




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/64, H04M 7/00, H04L 12/26		A1	(11) International Publication Number: WO 99/66682
			(43) International Publication Date: 23 December 1999 (23.12.99)
(21) International Application Number: PCT/US99/13585 (22) International Filing Date: 18 June 1999 (18.06.99) (30) Priority Data: 60/089,831 19 June 1998 (19.06.98) US 60/090,075 19 June 1998 (19.06.98) US 09/219,018 23 December 1998 (23.12.98) US (71) Applicant (for all designated States except US): NORTHERN TELECOM [US/US]; 2221 Lakeside Boulevard, Richardson, TX 75083 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): HO, Anthony [US/US]; 3568 Fitzsimmons Common, Fremont, CA 94538 (US). (74) Agents: SCHAAAL, William, W. et al.; Blakely, Sokoloff, Taylor & Zafman, 7th floor, 12400 Wilshire Boulevard, Los Angeles, CA 90025-1026 (US).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: METHOD AND APPARATUS FOR FALLBACK ROUTING OF VOICE OVER INTERNET PROTOCOL CALL



(57) Abstract

An apparatus causes alternate connection of a telephone call directed to an IP network if the quality of service provided by the IP network is less than a predetermined threshold. A network monitor measures a transmission rating factor for the IP network. A comparator, coupled to the network monitor, compares a desired transmission rating factor to the measured transmission rating factor for the IP network. An IP network interface, coupled to the comparator, an originating system, and the IP network, receives the telephone call for a dialed number from the originating system. The IP network interface causes the originating system to connect the telephone call through a first network if the measured transmission rating factor for the IP network is less than the desired transmission rating factor, and connects the telephone call through the IP network otherwise.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/13585

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9727692	A	31-07-1997	CA 2243655 A EP 0886936 A	31-07-1997 30-12-1998
US 5610910	A	11-03-1997	CA 2227474 A WO 9707625 A EP 0845186 A JP 10512418 T US 5828666 A	27-02-1997 27-02-1997 03-06-1998 24-11-1998 27-10-1998
GB 2300089	A	23-10-1996	AU 707903 B AU 5341896 A CA 2218687 A EP 0823182 A WO 9633583 A	22-07-1999 07-11-1996 24-10-1996 11-02-1998 24-10-1996
US 5553128	A	03-09-1996	NONE	

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/13585

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 610 910 A (LIVERMORE FREDERICK C ET AL) 11 March 1997 (1997-03-11) abstract column 1, line 1 -column 2, line 42 column 4, line 40 -column 5, line 12 column 7, line 10 -column 11, line 16 column 14, line 1-12 figures 1,7 ---	1,6,11
X	HOUGHTON T F ET AL: "A PACKET TELEPHONY GATEWAY FOR PUBLIC NETWORK OPERATORS" ISS. WORLD TELECOMMUNICATIONS CONGRESS. (INTERNATIONAL SWITCHING SYMPOSIUM),CA,TORONTO, PINNACLE GROUP, page 35-44 XP000704453 abstract page 35, right-hand column, line 21 -page 36, right-hand column, line 28 page 38, left-hand column, line 5 -page 40, right-hand column, line 25 page 41, left-hand column, line 9 -page 43, left-hand column, line 10 figures 3,4 ---	1,11
Y	GB 2 300 089 A (EUROTEL TELECOM LIMITED) 23 October 1996 (1996-10-23) abstract page 1, line 1-26 page 2, line 25 -page 3, line 32 page 4, line 35 -page 5, line 23 page 9, line 13-19 page 10, line 31 -page 12, line 2 page 12, line 27 -page 13, line 3 page 20, line 3-17 page 22, line 11 -page 24, line 4 figures 1,3 ---	2,3,7,8, 12,13
Y	US 5 553 128 A (GRIMES GARY J) 3 September 1996 (1996-09-03) column 1, line 41-58 column 3, line 22-49 -----	4,9,14

METHOD AND APPARATUS FOR FALLBACK ROUTING OF VOICE OVER INTERNET PROTOCOL CALL

CROSS-REFERENCES TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/089,831, filed June 19, 1998, which is incorporated herein by reference, and of U.S. Provisional Application No. 60/090,075, filed June 19, 1998, which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

This invention relates to connecting of telephone calls and, more particularly, to connecting of telephone calls over internet protocol networks.

2. Background Information

The traditional telephone network is a switched network that provides users with a dedicated end-to-end circuit for the duration of each call. Circuits are reserved between the originating switch, tandem switches (if any), and the terminating switch based on the called party number to create the end-to-end circuit.

Recently, telephone calls have been transmitted over digital networks using packet switched internet protocol (IP) networks, termed voice over IP (VoIP) transmission. Packet-switched IP networks provide shared, virtual circuit connections between users. Voice information to be transmitted across an IP network is converted into digital data and broken up into multiple, discrete packets. Individual packets may travel over different network paths to reach the final destination where the packets are reassembled in the proper sequence to reconstruct the original voice information. The transmission speed between any two users can change dramatically based on the dynamic number of users sharing the common transmission

medium, their bandwidth requirements, the capacity of the transmission medium, and the efficiency of the network routing and design.

VoIP transmission typically costs less than transmission over traditional public switched telephone networks (PSTNs). A disadvantage of VoIP networks is the variability of the quality of the signal received at the destination as determined by changing network conditions. The received signal quality depends on a large number of variable network factors such as packet loss, packet latency, queuing delay, and bandwidth availability. These network factors will vary depending on the volume of network traffic and the location of the destination. The IP network, unlike the traditional public switched network, is not uniformly or predictably suitable for voice quality transmission.

Prior art systems for connecting calls over IP networks have monitored the quality of service (QoS) provided by the network and disabled the gateway to the IP network when QoS fell below an acceptable level. However, QoS is not a uniform characteristic in an IP network. QoS is dependent on the destination and it may be unacceptable for transmissions to one destination but be acceptable to another destination. Accordingly, what is needed is a method and apparatus for monitoring the quality of service (QoS) of the IP network and connecting a telephone call over an alternate network, on a call by call basis, if the QoS of the IP network is unacceptable based on the destination for the call.

SUMMARY OF THE INVENTION

An apparatus causes alternate connection of a telephone call directed to an IP network if the quality of service provided by the IP network is less than a predetermined threshold. A network monitor measures a transmission rating factor for the IP network. A comparator, coupled to the network monitor, compares a desired transmission rating factor to the measured transmission rating factor for the IP network. An IP network interface, coupled to the comparator, an originating system, and the IP network, receives the telephone call for a dialed number from the originating system. The IP network interface causes the originating system to connect the telephone call through a first network if the measured transmission rating factor for the IP network is less than the desired transmission rating factor, and connects the telephone call through the IP network otherwise.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows an embodiment of the invention.

Figure 2 shows a second embodiment of the invention that uses an ISDN PRI interface.

Figure 3 shows a third embodiment of the invention that uses an analog trunk loop back path.

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides a method and apparatus for monitoring the quality of service (QoS) of the internet protocol (IP) network and connecting a telephone call over an alternate network, on a call by call basis, if the QoS of the IP network is unacceptable based on the destination for the call.

Figure 1 is an exemplary system for providing voice over IP (VoIP). The system includes a call processor 100 that receives a telephone call from a local user 110, including a destination telephone number, and a plurality of network interface cards 102, 104 to provide connections to networks 106, 108 capable of carrying telephone calls, including at least one network interface card 104 that provides a connection to an IP network 108. The call processor 100 uses the telephone number of the received call to consult a routing table 120 and identify a network interface card 102, 104 that can provide a connection for the telephone call.

A network interface card 104 that provides a connection to the IP network 108 and contains an embodiment of the present invention, will cause a call directed to the card to be redirected to a different network 106 if the QoS for the call will be below the desired threshold based on the destination of the call. The IP interface card 104 receives the call to be connected through the IP network 108 and a desired QoS for the call. The desired QoS may be received with the call, or in advance of the call as a general level of QoS desired, possibly based on one or more call characteristics. The IP network card 104 uses the destination of the call to be connected to consult statistics collected by a network monitor 122 that runs on the card. The statistics for the IP network 108 QoS to the destination of the call to be routed are compared to the desired QoS for the call. If the QoS that the IP network 108 has provided recently for test packets to the destination of the call to be routed is less than the desired QoS threshold, then the call is returned to the call processor 100 to be connected through another network 106. Otherwise, the call is connected through the IP network 108.

Figure 2 shows an embodiment of the invention in which the IP network card 204 is an integrated services digital network (ISDN) to IP gateway that provides a primary rate interface (PRI) to the call processor. In this embodiment, the IP network interface 204 sends an ISDN call reject signal to the call processor 100 if the call cannot be connected through the IP network 108 because of a low QoS. The call processor 100 will then use an alternate connection through another network interface 202 according to ISDN protocol.

Figure 3 shows another embodiment of the invention in which the IP network interface 304 emulates an analog trunk interface. In this embodiment, the IP network interface 304 contains a loop back path that allows the IP network interface 304 to send a call to the call processor 100. If the call cannot be connected through the IP network 108 because of a low QoS, the IP network interface 304 will connect the call to the call processor 100 through the loop back path and give the call a special number to force a connection through an alternate network 106. In one embodiment, the special number includes a special prefix, such as 9999, that is placed at the front of the original called number. When the call processor 100 receives the looped back call, it directs the call to an alternate network interface 302 because of the special called number that was attached to the call by the network card. The looped back call is not distinguishable from other calls received by the call processor 100 except for the special routing number. The following is an exemplary call setup sequence for fall back to PSTN of a call directed to the IP network in an embodiment of the invention emulating an analog trunk interface:

- Step 1: A user 110 calls a destination by dialing a number such as "6-570-1234";
- Step 2: The call processor 100 receives the call and, based on the prefix of the dialed number, the call processor 100 finds a matching entry in a routing table 120 and directs the call to the IP network interface 304;
- Step 3: The IP network interface 304 tests the QoS statistics generated by the network monitor 122 for the destination IP address of the call;
- Step 4: If the QoS is less than a supplied desired QoS threshold, the IP network interface 304 inserts the special prefix "9999" in the dialed number and connects the call to the call processor 100 through a loop back path;
- Step 5: The call processor 100 receives the call generated by the IP network interface 304 with the called party number of "6-9999-570-1234";
- Step 6: The call processor 100 finds a matching entry in the routing table 120 for the special prefix "9999," and, based on the routing information, the call processor deletes the first five digits and directs a call to "570-1234" to the PSTN network interface 302.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other modifications may occur to those ordinarily skilled in the art.

CLAIMS

What is claimed is:

1. An apparatus comprising:
a network monitor that measures a transmission rating factor for an IP network;
a comparator, coupled to the network monitor, that compares a desired transmission rating factor to the measured transmission rating factor for the IP network;
an IP network interface, coupled to the comparator, an originating system, and the IP network, that receives a telephone call for a dialed number from the originating system, and that causes the originating system to connect the telephone call through a first network if the measured transmission rating factor for the IP network is less than the desired transmission rating factor, and connects the telephone call through the IP network otherwise.
2. The apparatus of claim 1, where the IP network interface further replaces the dialed number with a special number based on the dialed number and connects the telephone call for the special number to the originating system if the measured transmission rating factor for the IP network is less than the desired transmission rating factor.
3. The apparatus of claim 2, where the IP network interface further appends the dialed number to a special fall back location code.
4. The apparatus of claim 1, where the IP network interface further returns an ISDN call reject signal to the originating system if the measured transmission rating factor for the IP network is less than the desired transmission rating factor.
5. The apparatus of claim 1, where the network monitor periodically measures transmission characteristics for test packets sent to a destination IP address associated with the telephone call.
6. A method of connecting a telephone call for a dialed number through one of a first network and an IP network, comprising:

receiving the telephone call to be connected from an originating system;
receiving a desired transmission rating factor;
measuring a transmission rating factor for the IP network;
comparing the desired transmission rating factor to the measured transmission rating factor for the IP network;
causing the originating system to route the telephone call through the first network if the measured transmission rating factor for the IP network is less than the desired transmission rating factor; and
connecting the telephone call through the IP network otherwise.

7. The method of claim 6, where causing the originating system to route the telephone call through the first network further comprises replacing the dialed number with a special number based on the dialed number and connecting the telephone call for the special number to the originating system.

8. The method of claim 7, where replacing the dialed number with the special number further comprises appending the dialed number to a special fall back location code.

9. The method of claim 6, where causing the originating system to connect the telephone call through the first network further comprises returning an ISDN call reject signal to the originating system.

10. The method of claim 6, where measuring the transmission rating factor further comprises periodically measuring transmission characteristics for test packets sent to a destination IP address associated with the telephone call.

11. A telephone system comprising:
a call processor that receives a telephone call including a dialed number and directs the telephone call to one of a plurality of network cards comprising a first network card and an IP network card;
the IP network card further comprising,
a network monitor that measures a transmission rating factor for an IP network;



a comparator, coupled to the network monitor, that compares a desired transmission rating factor to the measured transmission rating factor for the IP network;
an IP network interface, coupled to the comparator, the call processor, and the IP network, that receives the telephone call, and that causes the call processor to route the telephone call through the first network card if the measured transmission rating factor for the IP network is less than the desired transmission rating factor, and that connects the telephone call through the IP network otherwise.


12. The telephone system of claim 11, where the IP network interface further replaces the dialed number with a special number based on the dialed number and connects the telephone call for the special number to the call processor if the measured transmission rating factor for the IP network is less than the desired transmission rating factor.

13. The telephone system of claim 12, where the IP network interface further appends the dialed number to a special fall back access code.

14. The telephone system of claim 11, where the IP network interface further returns an ISDN call reject signal to the call processor if the measured transmission rating factor for the IP network is less than the desired transmission rating factor.

15. The telephone system of claim 11, where the network monitor periodically measures transmission characteristics for test packets sent to a destination IP address associated with the telephone call.

*Fig. 1**Fig. 2*

*Fig. 3*

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/13585

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04L12/64 H04M7/00 H04L12/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04L H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y	WO 97 27692 A (FIRETALK INC) 31 July 1997 (1997-07-31) abstract page 2, line 26 -page 5, line 2 page 7, line 1 -page 9, line 11 page 10, line 24 -page 11, line 16 page 12, line 16 -page 17, line 169 page 19, line 3-9 figure 4 --- -/--	1,5,6, 10,11,15 2-4,7-9, 12-14

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 November 1999

Date of mailing of the international search report

26/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel.: (+31-70) 340-2040, Tx. 31 651 epo.nl.
Fax: (+31-70) 340-3016

Authorized officer

Lievens, K